



## NP-30 Pager

- Six Cap Codes (Addresses)
- 16 Message Slots
- Full Function Self Test
- Program by RS232
- Message Display on LCD
- Message Time Stamping
- Message Full Indication
- Backlit Display
- Unread Message Indication
- Out of Range Indication

The NP-30 is a top-view numeric pager that combines multi-functionality and easy operation for your daily activities. With the powerful function of auto-save message when the pager is off or while the battery is being changed, you won't miss any important messages.

### Display

- Backlight: In low-light conditions, the backlight makes the screen easy to read.
- Capacity: 12 Digits and 4 icons on the LCD Screen.

### Indicator Alert

- Unread Message Indication
- Out of range Indication
- Low Battery Alert & Indication
- Message Full Indication

### Messaging

- Message Display on LCD
- Message Time Stamping
- Message Full Indication
- Selective Erase/ Erase All Message/s
- Saves Message when the pager is off or when changing the battery
- Unread Message Indication

### NP30 Specifications

	VHF	900 MHz
Frequency Range:	143 - 174MHz	450 - 470MHz
Transmission Speed:	512/1200/2400 bps	
Code Format:	POCSAG	
Paging Sensitivity(u/Vm):	Baud 512: <=5   Baud 1200: <=7   Baud 2400: <=9	
Modulation:	FSK+/-4.5Hz	
Channel Width:	12.5KHz	
Intermediate Frequency:	21.4MHz/455KHz	
Adjacent Channel Selectivity:	55dB@+/-255KHz	
Image Frequency Rejection:	40dB	
Spurious Response Rejection:	40dB	
Intermodulation Rejection:	50dB	
Alert Response:	75dB@30cm	
Ambient Working Temperature:	-10 ~ 55° c	
Battery:	1.5 V AA Alkaline x 1	
Dimension:	(L) 68mm x (W) 50mm x (H) 18mm	